

NBS SPEC

SHUTTER CURTAIN

Aluminium double skinned polyester powder-coated slat with polyurethane foam insulating core. Vented or non-vented options.

Colours: White, Brown, Beige, Grey as standard. Other colours available on request.

Blind Surface :: 42mm

Weight per m² :: 4kg

Maximum Width :: 3400mm

Maximum Surface :: 8m²

VERTICAL SIDE GUIDES / BOTTOM SLAT

The extruded aluminium bottom slat is fitted with a weather seal. Guide are available with a circular surface. 25mm, 45mm, 53mm, 60mm, or 68mm guide depths available on request. 53mm as standard. Self-packing guides are also available.

Colours: White, Brown, Grey. Other colours available on request.

ENCLOSURE / HOUSING

Manufactured from roll formed aluminium with a stove-enamelled finish in 2 sections with a 45° chamfered lid. Circular housing option. End caps are pressure-moulded aluminium alloy.

Colours: White, Brown, Grey. Other colours available on request.

Shutter Height (mm)	Box Size (mm)
870	138
1200	150
1600	165
1900	180
2500	205
4000	250

OPERATION

Cord: The swivel winder coils the belt when it is pulled up to a maximum weight of 20kg.

Rod and Crank: Geared rod and crank handle winds the shutter up to a weight of 25kg.

Spring and Lock: A counter-balanced spring assembly with a key-lock bottom slat & handles up to a weight of 30kg.

Electric: Single phase tubular motor & wall switch as standard. Numerous options such as group or remote control etc. Manual override facility as required.