

NBS Specification

Supplier

UK Roller Shutters and Garage Doors Ltd

Unit 41 Wombourne Enterprise Park

Wombourne

WV50AL

01384221 743

Product Code

CRPK-SR2

Performance

Certified to LPS 1175 issue 7

Security Rating Two (SR2)

Approved dimensions

Maximum certified width: 6.0m

Minimum certified width: 1.8m

Maximum certified height: 6.0m

Minimum certified height: 1.8m

Shutter curtain

Extruded aluminium lockdown profiles.

Finish as delivered: polyester powder coated in standard RAL/BS colour.

Bottom rail

Reinforced extruded aluminium section with strengthened core.

Finish as delivered: polyester powder coated in standard RAL/BS colour.

Frames/Guides

Heavy duty guide profiles anchored direct to the structure.

Finish as delivered: polyester powder coated in standard RAL/BS colour.

Substrate

Certified installation onto:

Brickwork

Blockwork

Concrete

Structural Steelwork

Operation

Motorised to allow controlled ascent and descent.

240v - Low duty cycle, or where limited to single phase supply.

415v - High duty cycle or for larger apertures.

Controls

Full range of compatible controls including push button switch, key switch, radio control or possible to integrated into building management systems and third party alarms.

Safety on close as assessment directs.