

# NBS Spec

## SHUTTER CURTAIN

Double-skinned 37mm extruded aluminium.

**Colours:** White & Brown as standard. Powder coating available

Blind Surface: 38mm

Weight per m<sup>2</sup>: 7.3kg

Maximum Width: 4000mm

Maximum Surface: 12m<sup>2</sup>

## VERTICAL SIDE GUIDES / BOTTOM SLAT

The extruded aluminium bottom slat is fitted with a weather seal. Guide are available with a circular surface. 25mm, 45mm, 53mm, 60mm, or 68mm guide depths available on request. Self-packing guides are also available.

**Colours:** White, Brown & Grey as standard. Powder coating available

## ENCLOSURE / HOUSING

Manufactured from roll-formed aluminium with a stove-enamelled finish. End caps are pressure moulded aluminium alloy.

**Colours:** White, Brown & Grey as standard. Powder coating available

Shutter Height (mm)	Box Height (mm)
1000	150
1600	165
1900	180
2900	205
3800	250
5000	300

## OPERATION

**Cord:** The swivel winder coils the belt when it is pulled up to a maximum weight of 20kg.

**Rod and Crank:** Geared rod and crank handle winds the shutter up to a weight of 25kg.

**Spring and Lock:** A counter-balanced spring assembly with a key-lock bottom slat & handles up to a weight of 30kg.

**Electric:** Single phase tubular motor & wall switch as standard. Numerous options such as group or remote control etc. Manual override facility as required.