

NBS Spec

SHUTTER CURTAIN

Aluminium double-skinned polyester powder coated slat with polyurethane foam insulating core.

Colours: White, Brown, Beige, Blue, Moss Green, Fir Green, Sage Green, Black, Red, Light Grey, Silver, Anthracite, Golden Oak, Teak, Rosewood as standard. Powder Coating and other finishes available.

Blind Surface :: 78mm

Weight per m² :: 5.5kg

Maximum Width :: 5500mm

Maximum Surface :: 16m²

VERTICAL SIDE GUIDES / BOTTOM SLAT

Bottom slat from extruded aluminium with EPDM weather seal. Guide channels with brush infill and a depth of 90mm, 70mm or 150mm.

Colours: White or brown. Other colours available on request.

ENCLOSURE / HOUSING

Manufactured from roll-formed aluminium with a stove-enamelled finish. End caps are pressure-moulded aluminium alloy.

Colours: White or brown as standard. Other colours available on request.

Shutter Height (mm)	Box Size (mm)
---------------------	---------------

2000	250
------	-----

3000	300
------	-----

4000	360
------	-----

OPERATION

Electric: Single phase tubular motor & wall switch as standard. Numerous options such as group or remote control etc. Manual override facility as required.

Note: Manual operation is available but not common for the ALU-12T77 profile as it is utilised for larger areas in most cases