

NBS Spec

ALU-1237PU

SHUTTER CURTAIN

Double-skinned 37mm punched extruded aluminium.

Colours: White & Brown as standard. Powder coating available

Blind Surface: 38mm

Weight per m2: 7.3kg

Maximum Width: 4000mm

Maximum Surface: 12m2

VERTICAL SIDE GUIDES / BOTTOM SLAT

The extruded aluminium bottom slat is fitted with a weather seal. Guide are available with a circular surface. 25mm, 45mm, 53mm, 60mm, or 68mm guide depths available on request. Self-packing guides are also available.

Colours: White, Brown & Grey as standard. Powder coating available

ENCLOSURE / HOUSING

Manufactured from roll-formed aluminium with a stove-enamelled finish. End caps are pressure moulded aluminium alloy.

Colours: White, Brown & Grey as standard. Powder coating available

Shutter Height (mm)	Box Height (mm)
1000	150
1600	165
1900	180
2900	205
3800	250
5000	300

OPERATION

Cord: The swivel winder coils the belt when it is pulled up to a maximum weight of 20kg.

Rod and Crank: Geared rod and crank handle winds the shutter up to a weight of 25kg.

Spring and Lock: A counter-balanced spring assembly with a key-lock bottom slat & handles up to a weight of 30kg.

Electric: Single phase tubular motor & wall switch as standard. Numerous options such as group or remote control etc. Manual override facility as required.