# **Expel Insect Screen**

## **APPLICATIONS**

Domestic and commercial sites requiring insect screen protection and good visibility. The Expel insect screen is designed for both small and large applications, making use of side zips which prevent the screen from slipping from the guide channels, aluminium bottom bar which locks into the guide channels, patented ClickOn system of attachment to the circular motor barrel, and unique screen welding technology which prevents folds and waves in the fabric and removes visible seams at the screen edges. Suitable for internal face or reveal fit.

### SCREEN

Warp and weft of 1mm spacing, 0.18x0.16mm thread, from 36% glassfibre and 64% PVC in grey or black. Screen practical thickness 0.33mm and 120g m<sup>2</sup>.

Minimum width: 800mm Minimum height: 800mm Maximum width: 5000mm Maximum height: 2600mm

### **ENCLOSURE**

Complete roll-formed aluminium box with pressure-moulded aluminium alloy end plates enclosing the insect screen in a single small but durable and secure enclosure. End plates slot into guide channels.

Finish: White, Brown, Silver, or Anthracite. Option to powder coat any RAL / BS colour (surcharge applies).

Overall Width (mm)	Plate Size (mm
2000	89
4000	103
5000	131

Plate sizes shown as a guide only and may vary.

## **BOTTOM SLAT**

Extruded aluminium bottom slat with rubber weather seal and end locks.

### **GUIDE CHANNELS**

Aluminium guide channels, polyester powder coated, with floating zip lock system from PVC. Width of 32mm.

Finish: White, Brown, Silver, or Anthracite. Option to powder coat any RAL / BS colour (surcharge applies).

#### **OPERATION**

Electric: Somfy tubular motor and wireless internal rocker switch as standard. Remote control handset, and a range of group control and multi-channel operation options also available.

CE compliant to all applicable directives and standards.

