

# NBS Spec

## SHUTTER CURTAIN

Double skinned polyester powder coated 100mm flat slat with polyurethane foam insulating core. Polycarbonate vision panels can be incorporated as required.

**Colour:** Galvanised finish as standard. Plastisol range or powder coating available.

Profile Height: 100mm

Weight per m<sup>2</sup>: 21kg

Maximum Width: 6500mm (Tubular motor), 12000mm (Outboard motor)

Maximum Surface: 14m<sup>2</sup> (Tubular motor), 72m<sup>2</sup> (Outboard motor)

## VERTICAL SIDE GUIDES / BOTTOM SLAT

Galvanised steel bottom slat with EPDM weather seal. Guide channel depth is 85mm as standard.

**Colour:** Galvanised finish as standard. Plastisol range or powder coating available.

**Note:** The guide channels are bolted to fixing angles or box section to suit the application.

## ENCLOSURE / HOUSING

Manufactured from 0.7mm or 0.9mm galvanised steel sheet. End caps are fabricated from 3mm steel.

**Colour:** Galvanised finish as standard. Plastisol range or powder coating available.

Shutter Height (mm)	Box Size (mm)
1500	400
2500	450
3250	500
4000	550
5000	600

**Note:** The above enclosure sizes are based on standard 3-phase motor operation.

## **OPERATION**

**Electric:** Single phase tubular motor or 3-phase outboard motor (dependent on curtain weight) with push button control.

Numerous options such as group or remote control etc available as required. Manual override facility as required. CE compliant to all applicable directives and regulations.