

NBS Spec

SHUTTER CURTAIN

Double skinned polyester powder coated 100mm flat slat with polyurethane foam insulating core. Perspex windows can be incorporated as required.

Colour: Galvanised finish as standard. Plastisol range or powder coating available.

Profile Height :: 100mm

Weight per m2 :: 16.5kg

Maximum Width :: 2,000mm

Maximum Surface :: 50M²

VERTICAL SIDE GUIDES / BOTTOM SLAT

Galvanised steel bottom slat with EPDM weather seal. Guide channel depth is 85mm as standard.

Colour: Galvanised finish as standard. Plastisol range or powder coating available.

Note: The guide channels are bolted to fixing angles or box section to suit the application.

ENCLOSURE / HOUSING

Manufactured from 0.7mm or 0.9mm galvanised steel sheet. End caps are fabricated from 3mm steel.

Colour: Galvanised finish as standard. Plastisol range or powder coating available.

Shutter Height (mm)	Box Size (mm)
2600	400
3500	450
4500	510

Note: The above enclosure sizes are based on standard 3-phase motor operation.

OPERATION

Electric: Single phase tubular motor or 3-phase outboard motor (dependent on curtain weight) with push button control.

Numerous options such as group or remote control etc available as required. Manual override facility as required. CE compliant to all applicable directives and regulations.